

# Wall mounted unit

FTXP-M



comfora

BLUEEVOLUTION



Practically inaudible



Energy saving during standby mode



3-D air flow



Online controller via app



Multi model application

Discreet wall mounted unit providing high efficiency and comfort

- › Practically inaudible: the unit runs so quietly, you will almost forget it is there.
- › Online controller (optional): control your indoor from any location with an app, via your local network or internet and keep an overview on your energy consumption
- › Silver allergen removal and air purifying filter: captures allergens such as pollen and dust

- › mites.
- › 3-D air flow combines vertical and horizontal auto swing to circulate a stream of warm or cool air right to the corners of even large spaces
- › The unit's compact dimensions makes it ideal for renovation projects, especially for above door installation

# FTXP-M + RXP-M




| Indoor unit          |                         | FTXP                             | 20M                 | 25M           | 35M           | 50M           | 60M           | 71M           |
|----------------------|-------------------------|----------------------------------|---------------------|---------------|---------------|---------------|---------------|---------------|
| Casing               | Colour                  |                                  | White               |               |               |               |               |               |
| Dimensions           | Unit                    | HeightxWidthxDepth               | 286x770x225         |               |               | 295x990x263   |               |               |
| Sound power level    | Cooling                 |                                  | 55                  |               | 58            | 59            | 60            | 62            |
| Sound pressure level | Cooling                 | High/Medium/Low/Silent operation | 39/33/25/19         | 40/33/26/19   | 43/34/27/20   | 43/39/34/27   | 45/41/36/30   | 46/42/37/32   |
|                      | Heating                 | Super high/High/Medium/Low/      | -/39/34/28/21       | -/40/34/28/21 | -/40/35/29/21 | 42/38/33/30/- | 44/40/35/32/- | 45/41/36/33/- |
| Control systems      | Infrared remote control |                                  | ARC480A53           |               |               |               |               |               |
|                      | Wired remote control    |                                  | BRC944B2 / BRC073A1 |               |               | -             |               |               |

| Efficiency data                    |                           | FTXP + RXP     | 20M + 20M      | 25M + 25M      | 35M + 35M      | 50M + 50M      | 60M + 60M         | 71M + 71M         |                   |
|------------------------------------|---------------------------|----------------|----------------|----------------|----------------|----------------|-------------------|-------------------|-------------------|
| Cooling capacity                   | Min./Nom./Max.            | kW             | 1.3/2.00/2.6   | 1.3/2.50/3.0   | 1.3/3.50/4.0   | 1.7/5.0/6.0    | 1.7/6.0/7.0       | 2.3/7.1/7.3       |                   |
| Heating capacity                   | Min./Nom./Max.            | kW             | 1.30/2.50/3.50 | 1.30/3.00/4.00 | 1.30/4.00/4.80 | 1.7/6.0/7.7    | 1.7/7.0/8.0       | 2.3/8.2/9.0       |                   |
| Power input                        | Cooling                   | Min./Nom./Max. | kW             | 0.31/0.50/0.72 | 0.31/0.65/0.72 | 0.29/1.01/1.30 | 0.320/1.385/1.826 | 0.332/1.824/2.980 | 0.449/2.689/3.274 |
|                                    | Heating                   | Min./Nom./Max. | kW             | 0.25/0.52/0.95 | 0.25/0.69/0.95 | 0.29/1.00/1.29 | 0.440/1.579/2.356 | 0.456/1.928/2.787 | 0.617/2.571/3.306 |
| Space cooling                      | Capacity                  | Pdesign        | kW             | 2.00           | 2.50           | 3.50           | 5.0               | 6.0               | 7.1               |
|                                    | Energy efficiency class   |                |                | A++            |                |                |                   |                   |                   |
|                                    | SEER                      |                |                | 6.79           | 6.92           | 6.62           | 7.30              | 6.82              | 6.20              |
| Space heating<br>(Average climate) | Annual energy consumption |                | kWh/a          | 103            | 126            | 186            | 240               | 308               | 401               |
|                                    | Capacity                  | Pdesign        | kW             | 2.20           | 2.40           | 2.80           | 4.60              | 4.80              | 6.20              |
|                                    | Energy efficiency class   |                |                | A++            |                |                |                   |                   |                   |
| Nominal efficiency                 | SCOPnet/A                 |                |                | 4.69           | 4.65           | 4.68           | 4.42              | 4.12              | 4.04              |
|                                    | Annual energy consumption |                | kWh/a          | 662            | 728            | 845            | 1,463             | 1,638             | 2,166             |
|                                    | EER                       |                |                | 4.02           | 3.83           | 3.49           | 3.61              | 3.29              | 2.64              |
|                                    | COP                       |                |                | 4.77           | 4.36           | 4.02           | 3.80              | 3.63              | 3.19              |

| Outdoor unit         |                         | RXP                    | 20M                  | 25M    | 35M                  | 50M         | 60M                | 71M  |
|----------------------|-------------------------|------------------------|----------------------|--------|----------------------|-------------|--------------------|------|
| Dimensions           | Unit                    | HeightxWidthxDepth     | 550x658x275          |        |                      | 734x870x373 |                    |      |
| Sound power level    | Cooling                 |                        | 60                   |        | 62                   | 61          | 63                 | 66   |
|                      | Heating                 |                        | 61                   |        | 62                   | 61          | 63                 | 65   |
| Sound pressure level | Cooling                 | High/Nom.              | 46/-                 |        | 48/-                 | -/47        | -/49               | -/52 |
|                      | Heating                 | High/Nom.              | 47/-                 |        | 48/-                 | -/49        |                    | -/52 |
| Operation range      | Cooling                 | Ambient                | Min.-Max.            | -10~46 |                      |             |                    |      |
| Operation range      | Heating                 | Ambient                | Min.-Max.            | -15~18 |                      |             |                    |      |
| Refrigerant          | Type/Charge/GWP         | kg/TCO <sub>2</sub> eq | R-32/0.55/0.37/675.0 |        | R-32/0.70/0.48/675.0 |             | R-32/1.15/0.78/675 |      |
| Power supply         | Phase/Frequency/Voltage | Hz/V                   | 1~/50/220-240        |        |                      |             |                    |      |

**Daikin Europe N.V.** Naamloze Vennootschap · Zandvoordestraat 300 · 8400 Oostende · Belgium · [www.daikin.eu](http://www.daikin.eu) · BE 0412 120 336 · RPR Oostende (Responsible Editor)



ECPEN19-046

02/19



Daikin Europe N.V. participates in the Eurovent Certified Performance programme for Liquid Chilling Packages and Hydronic Heat Pumps, Fan Coil Units and Variable Refrigerant Flow systems. Check ongoing validity of certificate: [www.eurovent-certification.com](http://www.eurovent-certification.com)

The present leaflet is drawn up by way of information only and does not constitute an offer binding upon Daikin Europe N.V. Daikin Europe N.V. has compiled the content of this leaflet to the best of its knowledge. No express or implied warranty is given for the completeness, accuracy, reliability or fitness for particular purpose of its content and the products and services presented therein. Specifications are subject to change without prior notice. Daikin Europe N.V. explicitly rejects any liability for any direct or indirect damage, in the broadest sense, arising from or related to the use and/or interpretation of this leaflet. All content is copyrighted by Daikin Europe N.V.